

Part number:

HYDROMA
HYDRAULICKÉ SYSTÉMY

HIDROMA
SYSTEMS
UKŁADY HYDRAULICZNE

HYDROMA
ГИДРАВЛИЧЕСКИЕ СИСТЕМЫ

PE

ISO 4401-03 AND ISO 4401-05 PLATES

p max 350 bar

Fixing screws and seals for mounting surface are supplied.

1 - BLANKING PLATES



dimensions in mm



name: PE3A-S1/10N (NBR seals) **code:** 1950351

name: PE3A-S1/10V (FPM seals) **code:** 1950355



ISO interface: ISO 4401-03
flow path configuration: all paths closed
material: aluminium
surface treatment: -
plate weight: 0,1 kg
fixing screws: 4 SHC M5x16 A8.8 zinc-plated
seals: 4 OR type 2037 (9.25x1.78) (90 Shore for NBR)




name: PE/D4-M (NBR seals) **code:** 1950042

name: PE/D4-M/V (FPM seals) **code:** 1950046

ISO interface: ISO 4401-05
flow path configuration: all paths closed
material: steel
surface treatment: phosphating black
plate weight: 0,43 kg
fixing screws: 4 SHC M6x20 A8.8 zinc-plated
seals: 5 OR type 2050 (12.42x1.78) (90 Shore for NBR)




2 - CONNECTION PLATES





name: PE3A-TA/10N (NBR seals) **code: 1950371**

name: PE3A-TA/10V (FPM seals) **code: 1950375**

ISO interface: ISO 4401-03
 nominal flow rate (Δp 5 bar): 50 l/min
 flow path configuration: P → A, B → T
 material: aluminium
 surface treatment: -
 plate weight: 0,1 kg
 fixing screws: 4 SHC M5x16 A8.8 zinc-plated
 seals: 2 OR type 2068 (17.17x1.78) (90 Shore for NBR)






dimensions in mm



name: PE3A-TB/10N (NBR seals) **code: 1950361**

name: PE3A-TB/10V (FPM seals) **code: 1950365**



ISO interface: ISO 4401-03
 nominal flow rate (Δp 5 bar): 50 l/min
 flow path configuration: P → B, A → T
 material: aluminium
 surface treatment: -
 plate weight: 0,1 kg
 fixing screws: 4 SHC M5x16 A8.8 zinc-plated
 seals: 2 OR type 2068 (17.17x1.78) (90 Shore for NBR)




name: PE3A-AB/10N (NBR seals) **code: 1950381**

name: PE3A-AB/10V (FPM seals) **code: 1950385**

ISO interface: ISO 4401-03
 nominal flow rate (Δp 5 bar): 50 l/min
 flow path configuration: A ↔ B
 material: aluminium
 surface treatment: -
 plate weight: 0,1 kg
 fixing screws: 4 SHC M5x16 A8.8 zinc-plated
 seals: 1 OR type 2081 (20.35x1.78) (90 Shore for NBR)



3 - INTERMEDIATE ADAPTOR PLATE



name: PC-D4/MD1-M code: 1950222

name: PC-D4/MD1-M/V code: 1950226

ISO interface: ISO 4401-05 to ISO 4401-03
 flow path configuration: through plate
 material: cast iron
 surface treatment: phosphating black
 plate weight: 0,86 kg
 fixing screws: 4 SHC M6x25 A8.8 zinc-plated
 seals: 5 OR type 2050 (12.42x1.78) (90 Shore for NBR)

dimensions in mm

